

Corotop® BLUE 140

The three- layer vapour permeable membrane highly resistant to mechanical damages and outside factors including UV- rays or high temperatures. It is characterised by high durability, guarantees comfort during application, even in difficult weather conditions. The product has also above-average technical parameters in its class.

Application:

- the membrane dedicated on roofs with full or part-boardings
- initial underlay for thermally insulated, ventilated, sloping roofs
- to be used to most types of roof coverage, particularly under ceramic, concrete and metal tiles

Advantages:

- minimizes heat loss
- regulates two-way vapour permeability
- protects thermoinsulation against damping
- enlarged grammature guarantees better mechanical resistance during installation and usage
- also available in version with 2 adhesive stripes (Corotop Blue 140+)



GRAMMATURE
140 g/m²



REACTION TO FIRE
CLASS E



VAPOUR
PERMEABILITY (SD)
0,02 m



RESISTANCE
TO WATER PENETRATION
CLASS W1



RESISTANCE TO UV
3 MONTHS



RESISTANCE TO TEARING
(NAIL SHANK) ALONG/ACROSS:
165 N / 230 N

Name	Size	Colour	Package
Corotop® BLUE 140	1,5m x 50r.m. = 75m ²	blue-anthracite	24 rolls
Corotop® BLUE 140+	1,5m x 50r.m. = 75m ²	blue-anthracite	24 rolls